# **High Pressure Grease Pump**

HFP 920.01.400 / HFP 920.01.700





The heavy duty high pressure grease pump is used for professional actuating of hydraulic clamping elements with grease nipple.

The pump allows a max. clamp pressure of 400 or 700 bar. A fixed adjusted relief valve avoids overload.

The perfect selected transmission ratio as well as precise lead of lever guaranteed a convenient working even at 700 bar pressure.

The pump is designed for the use of standardised grease cartridges of DIN 1284.

Clamp pressure can be read off the built-on swivelling pressure gauge.

### Technical data and particular criteria:

Working pressure max. 400 bar or 700 bar Test pressure 1000 bar Fluid quantity per stroke 0,35 ccm Pressure relief and grease feedback Swivelling pressure gauge connection Robust design Precise pressure adjusting Cylinder tube with chain Convenient and safe working Simple change of grease cartridge

#### **Delivery contains:**

- 1 x Metal bended pipe with HF coupling
- 1 x High pressure grease hose with HF coupling
- 1 x Pressure gauge with protection cap
- 2 x Grease cartridge with multi purpose grease
- 4 x Red follower cap for cartridge insert
- 1 x Transport box with foamed inlay

#### NORIS part no.:

HFP 920.01.400 HFP 920.01.700 Working pressure 0 - 400 bar Working pressure 0 - 700 bar

## **NORIS** ARMATUREN BURKENSTEIN GMBH & CO. KG - ABTEILUNG SPANNELEMENTE -

D-90411 Nürnberg Puscherstraße 3 Telefon: + 49 (0) 911/ 52 15 06 3 Telefax: + 49 (0) 911/ 52 24 40 E-Mail: noris@noris-armaturen.de Internet: www.noris-armaturen.de